

Lion Elastomers LLC

1615 Main Street • P.O. Box 667 • Port Neches, TX 77651 800 / 535-9960 • www.lionelastomers.com

## SBR 1732N Elastomer

# **Product Data**

SBR 1732N is an environmentally friendly version of SBR 1712 with higher bound styrene content, and aromatic extender oil replaced with a low Polycyclic Aromatic Hydrocarbon naphthenic oil. It was developed for tire applications.

#### **Unique Features**

- Cold polymerized styrene-butadiene elastomer
- Naphthenic oil extended

#### **Applications**

- Passenger & heavy-service treads
- Retread rubbers and bicycle tires

### **Typical Properties**

<u>Property</u>	<b>Test Method</b>	<u>Typical</u>
Bound Styrene, Weight %	ASTM D5775	30.5 - 33.5
Mooney viscosity, MML 1+4 (100°C)	ASTM D1646	41 - 51
Oil, Weight %	ASTM D5774	22.50 - 26.50
Oil Type	Naphthenic	
Organic acid, Weight %	ASTM D5774	3.6 - 6.0
Soap, Weight %	ASTM D 5774	0.5 Max.
Ash, Weight %	ASTM D5667	0.80 Max.
Volatile matter, Weight %	ASTM D5668	0.90 Max.
Emulsifier	_	Mixed acid
Coagulant	_	Acid
Stabilizer	_	Staining
Specific gravity, g/cc (bale)		0.95
Physical form*, lbs/bale	_	80.0 (36 kg)

SBR 1732N is an environmentally friendly version of SBR 1712 replacing aromatic extender oil with a naphthenic oil. It is recommended for applications such as passenger and heavy-service treads, retread rubbers, and bicycle tires.

**Note:** Antioxidant is added to this polymer to provide protection during manufacture and storage. The end user's process may require additional antioxidant protection.

Notice: All information supplied by or on behalf of Lion Elastomers LLC in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Elastomers LLC assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use made of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Elastomers LLC for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

SBR 1732N 7/17

<sup>\*</sup> This product is available in 80 lb rectangular bales individually wrapped in 1.5 mil, low melting point film and shipped in returnable aluminum OTD.