



Lion Copolymer Geismar, LLC

36191 Highway 30 • Geismar, LA 70734
800 / 535-9960 • www.lionelastomers.com

Trilene FreeFlow[®] 67

Product Data

A Free-Flowing Ethylene-Propylene-Ethylidene Norbornene
Low Molecular Weight Polymer on Silicon Dioxide

Trilene FreeFlow[®] 67 is a free-flowing polymer made by combining Trilene[®] liquid polymer and silica. The blend is nominally 68% ethylene-propylene copolymer and 32% silica. It is available as a dry, free-flowing powder that is easy to measure, store, and transfer. It incorporates quickly and thoroughly into various elastomer systems, and gives quality and processing advantages when compared to neat polymer. Trilene FreeFlow[®] 67 is effective in EPDM, BR, NR, SBR and other elastomers.

Typical Properties

Color	White to light tan
Silica content	32%
Volatiles at 100°C (212°F)	<0.5%
Specific Gravity	1.05
Molecular Weight, Da (GPC)	39,000
Degree of Unsaturation	
% Diene	9.5
Type	ENB
Ethylene/Propylene	46/54

9/2/20

Notice: All information supplied by or on behalf of Lion Copolymer Geismar, LLC in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Copolymer Geismar, LLC assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use made of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Copolymer Geismar, LLC for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.