



Lion Copolymer Geismar, LLC

36191 Highway 30 • Geismar, LA 70734
800 / 535-9960 • www.lionelastomers.com

Trilene[®] CP-600 Liquid Polymer

Product Data

An Ethylene-Propylene Liquid Copolymer

Description

Trilene[®] CP-600 is an intermediate low molecular weight ethylene-propylene liquid copolymer, randomly polymerized to produce a liquid elastomer with a stable, saturated hydrocarbon backbone. It has thermal and oxidation stability under normal conditions. Trilene[®] CP-600 can be used as a viscosity thickener for a wide range of lubricant products providing good shear stability and low temperature characteristics.

Typical Properties

Color	Colorless to Light Amber
Ash	<0.1%
Volatiles at 100°C (212°F)	<0.5%
Specific Gravity	0.85
Kinematic Viscosity at 100°C, cSt	600
Ethylene/Propylene	43/57
Molecular Weight (GPC)	8,000

08/20
TrileneCP600

Notice: All information supplied by or on behalf of Lion Copolymer Geismar, LLC in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Copolymer Geismar, LLC assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use made of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Copolymer Geismar, LLC for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.