



CUSHMAN®

ALL-NEW

HAULER® PRO ELITE™



DRIVING MORE UP-TIME.

The all-new Hauler PRO ELiTE with its remarkable range and zero-maintenance ELiTE Lithium powertrain is raising the bar for utility vehicles. Its reduced weight and lower operational costs will help you accomplish more and worry less.

ELiTE
LITHIUM

ELiTE
LITHIUM
POWERTRAIN

1500LB
TOWING
CAPACITY

50 MILES
PER BATTERY
CHARGE

1200LB
LOAD
CAPACITY



ALL-NEW CUSHMAN® HAULER® PRO ELITE™



STANDARD BRUSH GUARD



CARGO NET



VERSATILE DASH STORAGE

ELITE LITHIUM

- Zero Maintenance
- 5-year battery warranty
- Lightweight footprint
- More efficiency

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- Canopy Storage Net
- Brush Guard
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights
- LED Taillights
- E-Shield™ Frame
- Premium Steering Wheel (Standard)
- Premium Steering Wheel
- Side Body Color
- Windshield
- LED Headlights
- Glove Box
- Floor Mount Attachment

BODY & CHASSIS	
FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green
DIMENSIONS	
OVERALL LENGTH	119.0 in (302.26 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)
WHEEL BASE	77 in (195.5 cm)
FRONT WHEEL TRACK	35 in (88.9 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	4.5 in (11.4 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m ³)
POWER	
POWER SOURCE	56.7V Li-Ion Battery
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	14.9 HP (11.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary
BATTERY (QTY/TYPE)	4.2 ELITE - Twin Pack
BATTERY CHARGER	811 Watt World Charger
KEY OR PEDAL START	Pedal
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential with Helical Gears
SPEED CONTROLLER	350 Amp AC
GEAR SELECTION	Forward-Neutral-Reverse
REAR AXLE RATIO	17:1
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	926 lb (420 kg)
BED LOAD CAPACITY	800 lb (363 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
SPEED	16.5 mph ± .05 mph (26.5 kph ± 0.8 kph)
TOWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	18 x 8.5-8 (6 Ply Rated)