

LIVE LARGER



ALL-NEW

VALOR<sup>®</sup> 4



48V DC OR EX1  
CLOSED-LOOP EFI  
GAS ENGINE

12-VOLT MAINTENANCE  
FREE BATTERY

HEADLIGHTS &  
TAILLIGHTS



# VALOR® 4



**ELECTRIC**

**GAS**

## PROVEN PERFORMANCE WITH ADDED COMFORT.

The all-new EZGO® Valor 4 offers the versatility and flexibility to be tailored to your unique lifestyle. Experience a ride like no other that is quiet, yet powerful, with the first-of-its kind EX1 gas engine or 48-volt electric drivetrain. Now with room for 4, the Valor is the perfect way to rediscover the world around you with your family and friends.

### KEY FEATURES

- Turf Tires
- Headlights and Taillights
- Horn
- Storage Compartment
- New Rear Facing Seat for Added Storage and Comfort
- 48-Volt Battery Charger (Electric Only)
- State of Charge Meter (Electric Only)
- Closed-Loop EFI System (Gas Only)
- Fuel Gage (Gas Only)

### DIMENSIONS

OVERALL LENGTH	106 in (269cm)	
OVERALL WIDTH	47.0 in (119 cm)	
OVERALL HEIGHT (W/O ROOF)	47.6 in (120.9 cm)	49.5 in (126 cm)
OVERALL HEIGHT (W/ ROOF)	67.6 in (171.7 cm)	70.3 in (178 cm)
WHEEL BASE	66.0 in (168 cm)	
FRONT WHEEL TRACK	34.0 in (86 cm)	
REAR WHEEL TRACK	38.5 in (98 cm)	
GROUND CLEARANCE @ DIFFERENTIAL	4.5 in (11 cm)	5.0 in (12.7 cm)

### POWER

POWER SOURCE	48 Volt DC	4-Cycle, 9.15 cu in (150 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	Shunt Wound	N/A
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	3.0 hp (2.2 kW) Continuous	11.5 hp (8.6 kW) J1995 Standard
ELECTRICAL SYSTEM	48 Volt	Brushless DC Internal Starter Generator
BATTERIES (QTY./TYPE)	Six, 8 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Industrial-Rated Dry Filter
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	No Oil Filter
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	48 VDC QE, 120 VAC, UL & CSA	N/A
SPEED CONTROLLER	250 Amp Solid State Controller	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	12.44:1	11.47:1 (Forward) 14.35:1 (Reverse)

### PERFORMANCE

SEATING CAPACITY	4-Passenger	
DRY WEIGHT	720 lb (327 kg)	848 lb (385 kg) (without battery)
CURB WEIGHT	1088 lb (494 kg)	864 lb (392 kg)
VEHICLE LOAD CAPACITY	800 lb (363 kg)	
OUTSIDE CLEARANCE CIRCLE	19 ft (5.8 m)	
SPEED (LEVEL GROUND)	19 mph ± 0.5 mph (31 kph ± 0.8 kph)	

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	20 x 8 x 10 Turf Tire on Black Wheel

### BODY & CHASSIS

FRAME	Welded Steel with Powder-Coat Protection	
BODY & FINISH	Injection Molded TPO	
AVAILABLE BODY COLORS	Black, Flame Red	Black, Electric Blue, Platinum
AVAILABLE SEAT COLORS	Black, Tan	



www.ezgo.com

