



# MINUTE MISER™

## SWIFTLY MOVE AROUND ANY FACILITY.

Don't waste a minute of the workday with the energy-efficient 24V electric drivetrain Minute Miser. Equipped with simple handlebar steering, a 300-lb cargo deck that transforms into a rear seat, and a 550-lb total load capacity, the Minute Miser helps you to generate more productive operations.

**550LB**  
TOTAL LOAD CAPACITY

**HANDLEBAR**  
STEERING

**DIAMOND-PLATED**  
STEEL

**CONVERTIBLE**  
REAR SEAT



### OPTIONS & ACCESSORIES

- Portable Charger
- Certification Module EE
- Hour Meter
- Headlight
- Horn
- CE Certification

# MINUTE MISER™

## BODY & CHASSIS

|                |   |
|----------------|---|
| FRAME          | Welded Steel with DuraShield™ Powder Coat |
| BODY & FINISH  | Diamond Plate Poly Primer and Acrylic     |
| STANDARD COLOR | Safety Yellow                             |

## DIMENSIONS

|                       |                                  |
|-----------------------|----------------------------------|
| OVERALL LENGTH        | 85.0 in (216 cm)                 |
| OVERALL WIDTH         | 30.0 in (76 cm)                  |
| OVERALL HEIGHT        | 39.0 in (99 cm)                  |
| WHEEL BASE            | 48.0 in (122 cm)                 |
| WHEEL TRACK           | N/A Front / 25.5 in (65 cm) Rear |
| GROUND CLEARANCE      | 4.0 in (10 cm)                   |
| CARGO DECK DIMENSIONS | 23 in x 29 in (58 cm X 73 cm)    |
| CARGO DECK CAPACITY   | 300 lb (136 kg)                  |
| CARGO DECK MATERIAL   | Plywood                          |

## POWER

|                     |                                       |
|---------------------|---------------------------------------|
| POWER SOURCE        | 24V DC Series Wound                   |
| HORSEPOWER (KW)     | 8.25 hp (6.15 kW) @ 1570 rpm          |
| ELECTRICAL SYSTEM   | 24V DC                                |
| BATTERY (QTY/TYPER) | Four, 6V Deep Cycle                   |
| BATTERY CHARGER     | 24V DC, 100-240V AC On-Board, UL & CE |
| KEY OR PEDAL START  | Pedal                                 |
| SPEED CONTROLLER    | Solid State 250 Amp Rated             |
| DRIVE TRAIN         | Motor Shaft Direct Drive              |
| TRANSAXLE           | Differential w/ Helical Gears         |
| GEAR SELECTION      | Forward-Neutral-Reverse               |
| REAR AXLE RATIO     | 14.78:1                               |

## PERFORMANCE

|                          |                                     |
|--------------------------|-------------------------------------|
| SEATING CAPACITY         | 2-Person                            |
| WEIGHT W/O BATTERIES     | 440 lb (200 kg)                     |
| CURB WEIGHT              | 690 lb (313 kg)                     |
| VEHICLE LOAD CAPACITY    | 550 lb (250 kg)                     |
| BED LOAD CAPACITY        | 300 lb (136 kg)                     |
| OUTSIDE CLEARANCE CIRCLE | 10.8 ft (3.3 m)                     |
| SPEED                    | 10 mph ± 0.5 mph (14 kph ± 0.8 kph) |

## STEERING & SUSPENSION

|                      |   |
|----------------------|---|
| STEERING             | Direct Handlebar to Front Fork  |
| SUSPENSION           | Torque Block (Front) /<br>Coil Springs & Single Shock Absorber (Rear) |
| SERVICE BRAKE        | Rear Wheel Mechanical Drum  |
| PARKING BRAKE        | Single-Point Latch  |
| TIRES (FRONT & REAR) | 4.80 x 8 (Load Range B)   |

**CUSHMAN.COM**

©2022 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82326-G8 (Rev. 06/2022)

