

UNMATCHED PERFORMANCE MEETS NON-STOP PRODUCTIVITY.

With an 8.4 cubic-foot cargo bed, bench seating, lifted suspension, and turf tires, every part of the Hauler 800X is designed to go the extra mile, then go 50 more. Available with your choice of a fuel-efficient 13.5 hp EFI gas engine or an ELiTE lithium powertrain activated by Samsung SDI battery technology, the Hauler 800X gives you the longest-lasting ride on the fairway.



8.4 CU FT

CARGO BED

500LB

TOWING CAPACITY

725LB

VEHICLE LOAD CAPACITY

HIGHER GROUND

CLEARANCE

ZERO MAINTENANCE

ELITE LITHIUM BATTERY







ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger (ELiTE Only)
- Fuel/Oil Gauge (Gas Only)

CUSHMAN.COM

HAULER® 800X

HAULER 800X ELITE

HAULER 800X GAS

	\mathbf{P}		\sim	-	
BO	ЦΥ	~	GH.	м	 15

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green

DIMENSIONS

OVERALL LENGTH	110 in (279.4 cm)
OVERALL WIDTH	49 in (125 cm)
OVERALL HEIGHT	51 in (129.5 cm) (w/o Roof) / 74 in (188 cm) (w/ Canopy)
WHEEL BASE	65.5 in (166.4 cm)
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear
GROUND CLEARANCE	5.5 in (14.0 cm)
CARGO BOX CAPACITY	8.4 cu ft (0.24 m3)
CARGO BOX DIMENSIONS	28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)
CARGO BOX MATERIAL	Roto-Molded Polyethylene

POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 ci (401cc)	
VALVE TRAIN	N/A	Single Cylinder OHV	
HORSEPOWER (KW)	11.7 HP (8.7 kW) Peak	13.5 hp (10.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.	
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free	
KEY OR PEDAL START	Ped	dal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge	
LUBRICATION	N/A	Pressurized Oil System	
OIL FILTER	N/A	Spin-On	
COOLING SYSTEM	N/A	Air Cooled	
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank	
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission	
TRANSAXLE	Differential w/ Helical Gears		
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse	
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)	

PERFORMANCE

SEATING CAPACITY	2-Person (Bench)		
WEIGHT W/O BATTERIES	744 LB (351 KG)	800 lb (362.9 kg)	
CURB WEIGHT	821 lb (372 kg)	830 lb (376 kg)	
VEHICLE LOAD CAPACITY	725 lb (328.9 kg)		
BED LOAD CAPACITY	325 lb (147.4 kg)		
TOWING CAPACITY	500 lb (226.8 kg)		
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)		
SPEED	16.5 mph ± 0.5 mph	(26.5 kph ± 0.8 kph)	

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Rated)

