

NO JOB TOO BIG. NO JOB TOO SMALL.

Built with plenty of muscle, the Cushman® Hauler 4x4 Crew is equipped to attack your toughest jobs. An impressive 2,000-lb towing capacity, 1,500-lb vehicle payload, four-wheel independent suspension and a top speed of 25 mph, make the Hauler 4x4 Crew ideal for transporting crew and cargo around your facility. Stacked full of standard features including seatbelts, ROPS and doors, your crew will arrive safely, ready to work. The Hauler 4x4 Crew has what it takes to get the job done.

25 HP

DIESEL

6 PASSENGER


SEATING CAPACITY

2000 LB

TOWING CAPACITY

14.68 CU. FT

BED CAPACITYY





STANDARD FEATURES

- ROPS
- Headrest
- Seatbelts
- Half Doors
- Glove Box
- Multi-Function Display
- 12-Volt Outlet
- All Terrain Tires
- Side Fill Fuel Tank
- Headlights
- Taillights
- Brakelights
- Locking Rear Differential
- Horn
- Lower Brushguard
- Power Steering

OPTIONS & ACCESSORIES

- Glass Windshield
- Center Seat Console
- Underseat Storage
- Rear View Mirror
- Sun Visor
- Grille Guard
- Headlight Guard
- Rear Bumper Kit
- Back Up Alarm
- 4500 lb WARN Winch
- Overhead Console

COMMERCIAL PACKAGE

- Full Windshield with Air Vents
- Canopy
- Back Up Alarm
- Light Rail
- Beacon Light
- Turn Signals

CUSHMAN.COM

HAULER® 4X4 CREW

DIESEL

BODY & CHASSIS

DIMENSIONS	
STANDARD COLOR	Dynamic Charcoal
BODY & FINISH	TPO Molded in Color
FRAME	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat

OVERALL LENGTH	156.4 in (397.3 cm)
OVERALL WIDTH	63 in (160 cm)
OVERALL HEIGHT (W/ ROPS)	76.5 in (194 cm)
WHEEL BASE	118.5 in (301 cm)
FRONT WHEEL TRACK	51 in (129.5cm)
REAR WHEEL TRACK	51 in (129.5 cm)
GROUND CLEARANCE	12 in (30.48 cm)
CARGO BOX CAPACITY	14.68 cu ft (0.42 cu. m)

POWER

POWER TRAIN	25 HP (18.6 kW), 1.03L Liquid Cooled, 3 Cylinder Diesel Engine
VALVE TRAIN	3 Cylinder
HORSEPOWER (KW)	25 HP, 1028 cc
ELECTRICAL SYSTEM	12V, Alternator
BATTERY (QTY/TYPE)	One 12-Volt Maintenance Free
KEY OR PEDAL START	Key
OIL FILTER	Automotive, Screw On
COOLING SYSTEM	Liquid with Fan
FUEL CAPACITY	10 gal (37.9 L)
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	2/4WD Front, Selectable Locking Rear
GEAR SELECTION	Mechanical, Steering Column Mounted
FRONT/REAR AXLE RATIO	3.1:1

PERFORMANCE

SEATING CAPACITY	6 Person	
CURB WEIGHT	1,931 lb (902.1 kg)	
BED LOAD CAPACITY	1000 lb (453.6 kg)	
VEHICLE LOAD CAPACITY	1500 lb (680.4 kg)	
SPEED	25 mph (40.2 kph)	
TOWING CAPACITY	2000 lb (907.2 kg)	
OUTSIDE CLEARANCE CIRCLE	29.5 ft.	

STEERING & SUSPENSION

STEERING	Rack and Pinion, Tilt Steering Wheel
FRONT SUSPENSION	Double A-Arm with 10 in (25.4 cm) Travel
REAR SUSPENSION	Double A-Arm with 9.5 in (24.1 cm) Travel
SERVICE BRAKE	Dual Piston Front/Single Piston Rear Calipers
PARKING BRAKE	Parking Gear, Activated Via Shifter
TIRES (FRONT & REAR)	25 x 10.5 - 12 All Terrain

