

VALOR[®]



Start Your Journey.

The E-Z-GO[®] Valor is built for those that follow their own path. With endless opportunities to customize, the Valor will make every ride your own ride. The Valor has the power to get you where you need to go and lets you experience the world in a golf cart built for your lifestyle.

INTELLIBRAKE[™] TECHNOLOGY

AUTOMOTIVE-STYLE
PEDALS

INDEPENDENT FRONT SUSPENSION

EZGO[®]

VALOR[®]



Key Features

- 48V AC Powertrain or EX1 Closed-Loop EFI Gas Engine
- Automotive-Style Pedals
- Premium Steering Wheel
- Standard LED Headlights and Taillights
- Independent Front Suspension
- 20" Turf Tires
- IntelliBrake™ Technology with Automatic Parking Brake (Electric Only)
- State of Charge Meter (Electric Only)

Color Options

ELECTRIC



Black



Inferno Red

GAS



Bright White



Platinum



DIMENSIONS	ELECTRIC		EX1	
	VALOR 2	VALOR 4	VALOR 2	VALOR 4
OVERALL LENGTH	94.5 (240 cm)	105.5 in (268 cm)	94.5 (240 cm)	105.5 in (268 cm)
OVERALL WIDTH	47.0 in (119 cm)			
OVERALL HEIGHT (W/O ROOF)	47.5 (121 cm)	47.6 In (120.9 cm)	48.5 (124 cm)	49 in (125 cm)
OVERALL HEIGHT (W/ ROOF)	70 (178 cm)	67.6 in (171.7 cm)	71 (181 cm)	76 in (193 cm)
WHEEL BASE	65.7 (167 cm)			
FRONT WHEEL TRACK	35.5 (90 cm)			
REAR WHEEL TRACK	38 (97 cm)			
GROUND CLEARANCE @ DIFFERENTIAL	4.5 in (11 cm)		4 (10 cm)	

POWER		
MOTOR TYPE	48 Volt AC	Single Cylinder OHV, 4 Cycle, 9.15 cu in (150 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	4.4 hp (3.3 Kw) Continuous	11.5 hp (8.6 kW) J1995 Standard
ELECTRICAL SYSTEM	48 Volt	Brushless DC Internal Starter Generator
BATTERIES (QTY/TYPER)	Four, 12 Volt Lead Acid Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Industrial-Rated Dry Filter
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Removable Oil Screen
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.82 Gallon (22.3 L) Tank
BATTERY CHARGER	48 VDC QE, 120 VAC, UL & CSA	N/A
SPEED CONTROLLER	250 Amp Solid State Controller	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)

PERFORMANCE				
SEATING CAPACITY	2 or 4 Passenger			
DRY WEIGHT	635 lbs. (290 kg)	781 lbs. (355 kg)	676 lb (307 kg)	775 lb (352 kg)
CURB WEIGHT	935 lbs. (425 kg)	1136 lbs. (516 kg)	692 lb (314 kg)	791 lb (359 kg)
VEHICLE LOAD CAPACITY	800 lb (363 kg)			
OUTSIDE CLEARANCE CIRCLE	19 ft (5.8 m)			
SPEED (LEVEL GROUND)	19 mph ± 0.5 mph (31 kph ± 0.8 kph)	17 mph ± 0.5 mph (27 kph ± 0.8 kph)	19 mph ± 0.5 mph (31 kph ± 0.8 kph)	

STEERING & SUSPENSION		
STEERING	Double Ended Rack & Pinion	
SUSPENSION	Independent A-Arm Coil Over Shock (Front) - Mono-Lead Springs with Hydraulic Shocks (Rear)	
SERVICE BRAKE	Induction Motor	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement
TIRES	20 x 8 x 10 Turf Tire on Black Wheel	

BODY & CHASSIS		
FRAME	Welded Steel with Powder-Coat Protection	
BODY & FINISH	Injection Molded TPO	
AVAILABLE BODY COLORS	Black, Inferno Red	Platinum, White
AVAILABLE SEAT COLORS	Stone Beige, Black	



IT'S GOOD TO GO

EZGO.com