



E-Z-GO® RXV®

GAME-CHANGING INNOVATIONS

The E-Z-GO RXV's exclusive technology, rugged reliability and sophisticated style offer you premium performance and lower operating costs, and your golfers a superior on-course experience. Choose the energy-saving efficiency of our patented AC drive with full-time regenerative braking and an industry-leading battery warranty, or our best-in-class 13.5-hp gas-powered model.



A Textron Company



E-Z-GO RXV

With a patented, highly efficient 48-volt AC electric drivetrain or powerful 13.5-hp Kawasaki® gas-powered engine, an innovative parking brake that automatically engages when the vehicle stops (electric only), rack-and-pinion steering, independent front suspension, and a full complement of intelligent options and accessories, the RXV makes your operation more efficient and your guest experience the best it can be. The RXV will have the golfers coming back to your course for round after round.



Optional Fold-Down Windshield



Energy Transfer Bumpers



Integrated Cup, Ball & Tee Holders

Optional Cooler



18-in Turf Tires

OUR COMMITMENT TO **green**

- ▶ Electric model features quiet, zero-emissions 48-volt electric drivetrain
- ▶ Gas-powered model features a 13.5-hp Kawasaki® engine with hemispheric combustion chamber for better fuel economy (exceeds EPA/CARB standards)
- ▶ Foam seating made of 100% recycled materials
- ▶ Sloped surface design requires less water when cleaning
- ▶ Repairable seat components minimize landfill usage
- ▶ Utilizes recyclable plastic components
- ▶ Manufactured in ISO 14001-certified facility



A Textron Company

STANDARD FEATURES

- ▶ 18-in turf tires
- ▶ Ergonomic console
- ▶ Integrated cup, ball & tee holders
- ▶ Sweater basket
- ▶ Energy transfer bumpers

POPULAR OPTIONS & ACCESSORIES

- ▶ Fold-down windshield
- ▶ Sun canopy
- ▶ Weather enclosure
- ▶ Bag cover kit
- ▶ Wheel covers (silver spoke & gold spoke)
- ▶ Sand bucket
- ▶ Sand rake
- ▶ Club & ball washer
- ▶ Cooler
- ▶ Fender scuff guard
- ▶ Message holder
- ▶ Cleet cleaner
- ▶ Side basket
- ▶ Permanent & temporary tow bars
- ▶ Ashtray
- ▶ Hour meter
- ▶ CE kit
- ▶ Battery watering system (electric only)
- ▶ Handheld diagnostic unit (electric only)



FRONT



BACK



ELECTRIC

GAS

	ELECTRIC	GAS
DIMENSIONS		
Overall Length	94.5 in (240 cm)	94.5 in (240 cm)
Overall Width	47 in (119 cm)	47 in (119 cm)
Overall Height (w/o roof)	45.7 in (116 cm) (top of steering wheel)	45.7 in (116 cm) (top of steering wheel)
Overall Height (w/ roof)	68.5 in (174 cm) (top of sun canopy)	68.5 in (174 cm) (top of sun canopy)
Wheel Base	65.7 in (167 cm)	65.7 in (167 cm)
Front Wheel Track	35.5 in (90 cm)	35.5 in (90 cm)
Rear Wheel Track	38 in (97 cm)	38 in (97 cm)
Ground Clearance @ Differential	4.5 in (11 cm)	3.3 in (8 cm)
POWER		
Power Source	48 Volt DC	4-cycle 24.5 cu in (401 cc) Low Emissions
Valve Train	N/A	Single-Cylinder OHV with Hemispheric Combustion Chamber
Motor Type	48 Volt AC	N/A
Horsepower (kW)	4.4 hp (3.3 kW) Continuous	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
Electrical System	48 Volt	Starter/Generator — Solid State Regulator
Batteries (qty/type)	Four, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal	Pedal
Air Cleaner	N/A	Remote Intake, Industrial-Rated Dry Filter
Lubrication	N/A	Pressurized Oil System
Oil Filter	N/A	Spin-On
Cooling System	N/A	Air Cooled
Fuel Capacity	N/A	5.9 gallons (22.3 L)
Battery Charger	48VDC High Frequency UL/CSA	N/A
Speed Controller	235 Amp AC Controller	N/A
Drivetrain	Motor Shaft Direct Drive	Automatic, Continuously Variable Transmission (CVT)
Transaxle	Limited Slip Differential	Differential with Helical Gears
Gear Selection	Key Switch	Forward-Reverse
Rear Axle Ratio	16.99:1	11.42:1 (Forward) 15.78:1 (Reverse)
PERFORMANCE		
Seating Capacity	2-Person	2-Person
Dry Weight (w/o batteries)	635 lb (290 kg)	697 lb (316 kg)
Curb Weight	935 lb (425 kg)	747 lb (339 kg)
Vehicle Load Capacity	800 lb (360 kg)	800 lb (360 kg)
Outside Clearance Circle	19.2 ft (5.8 m)	19 ft (5.8 m)
Speed (level ground)	8-15 mph (13-24 kph) Programmable	12 mph ± 0.5 mph (19.3 kph ± 0.8 kph)
Towing Capacity	3 E-Z-GO Golf Cars with Approved Permanent Tow Bar	3 E-Z-GO Golf Cars with Approved Permanent Tow Bar
STEERING & SUSPENSION		
Steering	Double-Ended Rack and Pinion	Double-Ended Rack and Pinion
Front Suspension	Independent A-Arm Coil Over Shock	Independent A-Arm Coil Over Shock
Rear Suspension	Mono-Leaf Spring w/Hydraulic Shocks	Mono-Leaf Spring w/Hydraulic Shocks
Service Brake	Induction Motor	Rear Wheel Mechanical, Self-Adjusting Drums
Parking Brake	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement
Tires	Hole-In-One 18 X 8.50-8 (4-Ply Rated)	Hole-In-One 18 x 8.50-8 (4-Ply Rated)
BODY & CHASSIS		
Frame	Welded Steel with Powder-Coat Protection	Welded Steel with Powder-Coat Protection
Body & Finish	Injection Molded TPO	Injection Molded TPO
Standard Body Color	Forest Green, Ivory	Forest Green, Ivory
Optional Body Colors	Almond, Barley Gold, Black, British Racing Green, Burgundy, Electric Blue, Flame Red, Inferno Red, Java Brown, Metallic Charcoal, Oasis Green, Patriot Blue, Platinum, Steel Blue, Sunburst Orange (custom colors available)	Almond, Barley Gold, Black, British Racing Green, Burgundy, Electric Blue, Flame Red, Inferno Red, Java Brown, Metallic Charcoal, Oasis Green, Patriot Blue, Platinum, Steel Blue, Sunburst Orange (custom colors available)
Standard Seat Color	Stone Beige	Stone Beige
Optional Seat Colors	Oyster (custom colors also available)	Oyster (custom colors also available)
Pinstripe Colors	Pewter	Pewter



A Textron Company

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2013 E-Z-GO Division of Textron Inc. All rights reserved. 822013-G6