

HAULER™ PRO

ELECTRIC AC
UTILITY VEHICLE

72 Volt AC Electric Drivetrain

1,000-lb Load Capacity

9.6 cu-ft Cargo Box Capacity

72v
ELECTRIC

1000 lb
MAX
LOAD

1262 lb
MAX
TOW

9.6 CU FT
BED
CARGO



Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

CUSHMAN™



CUSHMAN™
LET'S WORK!

Fully loaded and ready to work all day long.

Whether you are looking to move people or equipment, the Hauler™ PRO gives you the flexibility to go farther and work longer hours. Powered by a quiet, zero emissions 72-volt AC electric drivetrain, the Cushman Hauler PRO features a daily range of at least 50 miles, low vehicle maintenance, a 9.6-cubic foot cargo bed and a total capacity of 1,000 pounds. An optional limited-slip differential provides for greatly improved traction on wet or loose turf, while helping to protect turf from damage due to wheel slippage. When your site needs the strong, silent type, look to the Cushman Hauler Pro.



VEHICLE LOAD CAPACITY
1,000 lb



VEHICLE WIDTH
49.8 in

HAULER PRO ELECTRIC AC UTILITY VEHICLE

DIMENSIONS	
Overall Length	111 in (281 cm)
Overall Width	49.8 in (126 cm)
Overall Height w/o Roof	47.5 in (121 cm) (Top of steering wheel)
Overall Height w/Struts & Roof	70.8 in (180 cm)
Wheel Base	75.3 in (191 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.8 in (99 cm)
Ground Clearance	5.5 in (14 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity & Material	9.6 cu ft (0.27 m ³) / Roto-molded polyethylene
POWER	
Power Source	72-Volts DC
Motor Type	AC Induction
Horsepower (kW)	22.4HP (16.7 kW) - Measured at Peak Torque
Electrical System	72 Volt
Batteries (Qty, Type)	Nine, 8-Volt Deep Cycle
Drive Train	Motor Shaft Direct Drive
Battery Charger	900 Watt 72V DC
Speed Controller	350 Amp AC
Gear Selection	Seatwrap Mount Forward-Neutral-Reverse Switch
Transaxle	Differential with Helical Gears
Rear Axle Ratio	17:1
PERFORMANCE	
Seating Capacity & Style	2-Person, Bench
Dry Weight	804 lb (365 kg) (Without Batteries)
Curb Weight (w/ Batteries)	1371 lb (622 kg)
Bed Load Capacity	600 lb (270 kg)
Vehicle Load Capacity	1000 lb (450 kg)
Outside Clearance Circle	22.1 ft (6.7 m)
Speed (level ground)	13 mph +/- 0.5 mph (21 kph +/- 0.8 kph)
Programmable Speed Range	5 - 19 mph (8 - 30.5 kph)
Towing Capacity	1262 lb (5,614 N) Max Drawbar
STEERING & SUSPENSION	
Steering	Self-compensating Rack & Pinion
Front Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Rear Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-adjusting Drum
Parking Brake	Self-compensating, Single Point Engagement
Front Tires	20 x 8 - 10 (4 Ply Rated)
Rear Tires	20 x 8 - 10 (4 Ply Rated)
FRAME & COLOR	
Frame	Powder Coated Welded Steel
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base Coat/Clear Coat
Standard Color	Forest Green

Factory Installed Options & Field Accessories

- Limited Slip Differential
- Locking Glove Box
- Windshield
- Roof
- Taillights
- Brakelights
- Trailer Dump (Steel and Poly)
- 14.9 cu ft aluminum cargo bed
- 12 Volt Outlet
- Body Color (Patriot Blue, Ivory, White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure
- Defroster/Fan
- Steel Cab
- Beacon