

# SAFETY DATA SHEET

Revision Date: 02/10/2016

Version 3.0

# 1888

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name 1888

Lion Elastomers Customer Service Number 1-800-535-9960

P.O. Box 667 Email Customerservice@lionelastomers.com

Port Neches, Texas 77651 Emergency telephone number CHEMTREC 1-703-527-3887

### 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Appearance: Solid bale, black

WARNING! MAY CAUSE ALLERGIC SKIN REACTION.

## **Potential Health Effects**

#### **Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

#### **Eve contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

#### Skin contact

Unlikely to cause skin irritation or injury. May cause allergic skin reaction.

#### Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

#### Inhalation

Breathing of vapor or mist is possible. It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

#### **Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

### **Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the



Version 3.0

## SAFETY DATA SHEET

# 1888

material through the skin may include:, irritation (nose, throat, airways), Cough, Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult

breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

#### **Target Organs**

No data

### Carcinogenicity

Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by The International Agency for Research on Cancer (IARC). Epidemiological studies of the incidence of cancer, cardiovascular or respiratory disease in workers in the carbon black producing industry have shown no significant health effects due to occupational exposure to carbon black.

#### Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

#### Other information

Prolonged exposure to smoke or fumes generated by heating this product may cause respiratory irritation with throat discomfort, coughing, or breathing difficulty. Repeated exposure may lead to respiratory sensitization (asthma) in susceptible individuals

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous Components CAS No. Concentration

CARBON BLACK	1333-86-4	>=30-<40%
EXTRACTS, PETROLEUM, RESIDUAL OIL	64742-10-5	>=20-<30%
SOLVENT		
ROSIN, POTASSIUM SALT	61790-50-9	>=1.5-<5%

#### 4. FIRST AID MEASURES

#### **Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**Skin** First Aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.



Version 3.1

### SAFETY DATA SHEET

#### 1888

### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Notes to physician

**Hazards**: No information available. **Treatment**: No information available.

#### **5. FIREFIGHTING MEASURES**

#### Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray

#### **Hazardous combustion products**

carbon dioxide and carbon monoxide. Polymers decompose under fire conditions. The smoke may contain polymer fragments of varying composition and unidentified toxic and/or irritating compounds.

# **Precautions for fire-fighting**

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

### NFPA Flammable and Combustible Liquids Classification

not applicable

#### **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

### **Environmental precautions**

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

#### Methods for cleaning up

Page 3 / 9



Version 3.1

## SAFETY DATA SHEET

### 1888

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

#### Other information

Comply with all applicable federal, state, and local regulations.

## 7. HANDLING AND STORAGE

#### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

#### **Storage**

Store in original container, Store in cool place, Keep away from direct sunlight. Keep at temperatures between 0 and 60°C.

٠

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

CARBON BLACK		1333-86-4	
NIOSH	Recommended exposure limit (REL):	0.1 mg/m3	
NIOSH	Recommended exposure limit (REL):	3.5 mg/m3	
OSHA Z1	Permissible exposure limit	3.5 mg/m3	
ACGIH	time weighted average	3 mg/m3	Inhalable fraction.
EXTRACTS, PETROLE SOLVENT	EUM, RESIDUAL OIL	64742-10-5	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities. Page 4 / 9



Version 3.1

## SAFETY DATA SHEET

#### 1888

#### **Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

### Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Discard gloves that show tears, pinholes, or signs of wear.

#### **Respiratory protection**

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	solid
Form	bale
Color	black
Odor	characteristic
Flash point	
	not applicable
Density	1.01 – 1.14 g/cm3

## 10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat

Incompatible products

Page 5 / 9



Version 3.1

## **SAFETY DATA SHEET**

1888

Oxidizing agents

### **Hazardous decomposition products**

carbon dioxide and carbon monoxide

#### **Hazardous reactions**

Product will not undergo hazardous polymerization.

## 11. TOXICOLOGICAL INFORMATION

Information on likely routes of

exposure

: Inhalation

Skin absorption

Skin contact Eye Contact Ingestion

**Product** 

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation : no data available

Serious eye damage/eye

irritation

: no data available

Respiratory or skin sensitisation : no data available

Components:

.

**CARBON BLACK:** 

Acute oral toxicity : LD 50 Rat: > 10,000 mg/kg

Page 6 / 9



Version 3.1

## SAFETY DATA SHEET

1888

Acute dermal toxicity : LD 50 Rabbit: > 3 g/kg

**EXTRACTS, PETROLEUM, RESIDUAL OIL SOLVENT:** 

Acute oral toxicity : LD 50 Rat: > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 Rat: > 5 mg/l

Exposure time: 4 h

Method: OECD Test Guideline 403

Aerosol

Acute dermal toxicity : LD 50 Rabbit: > 3,000 mg/kg

Method: OECD Test Guideline 402

Respiratory or skin sensitisation : Test Method: Buehler Test

Species: guinea pig

Result: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

**ROSIN, POTASSIUM SALT:** 

Acute oral toxicity : LD 50 Rat: > 2,000 mg/kg

Based on similar product.

Acute dermal toxicity : LD 50 Rat: > 2,000 mg/kg

Based on similar product.

Respiratory or skin sensitisation : Species: mouse

Classification: Did not cause sensitisation on laboratory animals.

Result: Did not cause sensitisation on laboratory animals.

Method: Local lymph node assay

### 12. ECOLOGICAL INFORMATION

### Ecotoxicity Product:

no data available

#### **Components:**

No data available

Page 7 / 9



Version 3.1

## **SAFETY DATA SHEET**

1888

Persistence and degradability

**ROSIN, POTASSIUM SALT:** 

Biodegradability : Biodegradation: 89.5 %

Method: OECD Test Guideline 302B

Bioaccumulative potential

**Product:** 

no data available

Components:

**ROSIN, POTASSIUM SALT:** 

Partition coefficient: n- octanol/water log Pow: 3 - 7

Mobility in soil

**Product:** 

no data available

**Components:** 

no data available

## 13. DISPOSAL CONSIDERATIONS

## Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### **REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT/
					LTD. QTY.



Version 3.1

# **SAFETY DATA SHEET**

# 1888

U.S. DOT - ROAD	
Not dangerous goods	
U.S. DOT - RAIL	
Not dangerous goods	
U.S. DOT - INLAND WATERWAYS	
Not dangerous goods	
TRANSPORT CANADA - ROAD	
Not dangerous goods	
TRANSPORT CANADA - RAIL	
Not dangerous goods	
TRANSPORT CANADA - INLAND WATERWAYS	
Not dangerous goods	
INTERNATIONAL MARITIME DANGEROUS GOODS	
Not dangerous goods	
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO	
Not dangerous goods	
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER	
Not dangerous goods	
MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARI	DOUS MATERIALS AND WASTES
Not dangerous goods	
*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID	
Dangerous goods descriptions (if indicated above) may not reflect quarthat can be applied. Consult shipping documents for descriptions that a	
15. REGULATORY INFORMATION	
California Prop. 65	
WARNING! This product contains a chemical known to the State of	Carbon black
California to cause cancer.	



Version 3.1

## SAFETY DATA SHEET

#### 1888

SARA Hazard Classification SARA 311/312 Classification

Acute Health Hazard

#### SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Notification status**

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic	y (positive listing)
Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Japan. ENCS - Existing and New Chemical Substances Inventory	n (negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear	y (positive listing)
Waste Control Act	2.
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	2	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard		

#### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

Page 10 /



Version 3.1

# **SAFETY DATA SHEET**

### 1888

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

**DOT**: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System