

Lion Elastomers Orange, LLC

5713 Farm to Market Rd 1006 • Orange, TX 77630 800 / 535-9960 • www.lionelastomers.com

Diene[™] 55AC10

Product Data

Diene[™]55AC10 is a solution polymerized plastics grade medium cis polybutadiene, featuring excellent color and low gel. It is intermediate in solution viscosity and contains a non-volatile antioxidant system. Diene[™]55AC10 is widely used as an impact modifier for thermoplastic resins such as HIPS and ABS.

Typical Properties

Test Method*	Typical Range
ASTM D5668	0.0 - 0.60
ASTM D1646	48.0 - 56.0
ASTM D445	147.0 – 177.0
ASTM D5667	0.20 Max.
ASTM E1356	- 96.0
ASTM D1209	0.0 - 5.0
	0.01 Max.
	4.0 Max.
	Non-staining
	None
	None
	0.90
	ASTM D5668 ASTM D1646 ASTM D445 ASTM D5667 ASTM E1356

- * This product is available in 75.0-pound rectangular bales individually wrapped with 3.0 mil polystyrene film. This material can be shipped in either returnable or disposable containers.
- * Antioxidant is added to this polymer to provide protection during manufacture and storage. The end user's process may require additional antioxidant protection.

Notice: All information supplied by or on behalf of Lion Elastomers Orange, LLC in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but Lion Elastomers Orange, LLC assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use made of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Lion Elastomers Orange, LLC for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.